

PRODUCT NAME: JOKISCH LB-100W 12 OZ
 PRODUCT CODE: 911345.00-12

HMIS CODES: H F R P
 1*1 1 X

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: Intercon Enterprises Inc.
 ADDRESS: 11-7750 River Rd. Delta, BC V4G 1C8 Canada
 EMERGENCY PHONE: Call Chemtrec 1-800-424-9300 (spill, leak, fire, accident)
 DATE PRINTED: 9/24/2010
 INFORMATION PHONE: 1-800-665-6655
 NAME OF PREPARER: Rudd Company, Inc.

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
PROPYLENE GLYCOL ACGIH TLV: Not Est. OSHA PEL: Not Est. Other: 400 ppm	57-55-6		2
TRIHYDROXYTRIETHYLAMINE ACGIH TLV: 5 mg/m3 OSHA PEL: Not Est.	102-71-6	10 205	2

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: 370 - 635
 VOC % BY WEIGHT: 3.5
 MIR: .0964
 SPECIFIC GRAVITY: .96
 VAPOR DENSITY: Heavier than air.
 EVAPORATION RATE: Slow (compared to n-butyl acetate)
 SOLUBILITY IN WATER: Appreciable
 APPEARANCE AND ODOR: Mild odor.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: 218 METHOD USED: theoretical
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.3 UPPER: 12.5
 EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG
 SPECIAL FIREFIGHTING PROCEDURES:

Evacuate all unnecessary personnel. Use full-protective equipment including self-contained breathing apparatus. Use water spray, preferably fog, to cool closed containers to prevent pressure build-up and possible explosion. Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams or waterways.

UNUSUAL FIRE AND EXPLOSION HAZARDS:
 Contents under pressure. Exposure to heat or prolonged exposure to sun may cause bursting.

===== SECTION V - REACTIVITY DATA =====

STABILITY:
 Stable
 CONDITIONS TO AVOID:

VENTILATION:

USE ONLY WITH ADEQUATE VENTILATION. Open all doors and windows to achieve cross-ventilation, in work and surrounding areas, during and after application until all vapors (fumes) are gone.

HAND PROTECTION:

Wear gloves to avoid skin contact. EYE PROTECTION:

Wear safety glasses or goggles to protect eyes from splash and spray mists. Note: Contact lenses may contribute to the severity of an eye injury and should not be worn when working with chemical products.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear protective clothing to avoid skin contact with liquid or mists.

WORK/HYGIENIC PRACTICES:

Wash hands after using and before eating, drinking or using tobacco products. Thoroughly clean contaminated clothing and shoes before reuse.

===== SECTION IX - SPILL AND LEAK PROCEDURES =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate ignition sources and ventilate area. Evacuate unnecessary personnel. Wear full protective equipment. Dike and contain spill with inert material. Transfer liquid to containers for disposal or recovery. Prevent material from entering storm drains or sanitary sewers and open bodies of water.

WASTE DISPOSAL METHOD:

Waste material and empty containers must be disposed of in accordance with all local, state and federal environmental control regulations. Use only approved waste management facilities.

===== SECTION X - SPECIAL PRECAUTIONS =====

KEEP OUT OF REACH OF CHILDREN.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep liquid spray and vapors away from heat, sparks and flame. Turn off or remove all sources of ignition. Use proper methods of ventilation to prevent vapor build-up. Avoid spraying hot surfaces. Avoid breathing vapors, spray mists and sanding or grinding dusts. Avoid contact with eyes and skin. Do not take internally. Use adequate methods of ventilation, respiratory and personal protective equipment. Do not reuse, weld, drill or heat empty containers which may contain explosive vapors. Follow label warnings until thoroughly cleaned or sent for disposal. Do not heat, puncture or incinerate containers. Contents are under pressure and may contain vapors even when empty. Do not remove or deface label.

OTHER CAUTIONS:

Contents under pressure. Do not store above 120 deg. F (50 deg. C) or permit prolonged exposure to sunlight. Protect containers from damage. Store in buildings or areas designed and protected for storage of aerosols.

===== SECTION XI - DISCLAIMER =====

DISCLAIMER: THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.