

PRODUCT NAME: Jokisch LB-100W 12 oz
PRODUCT CODE: 911345.00-12

H F Ph P
1*1 1 X

=====
SECTION I - MANUFACTURER IDENTIFICATION
=====

MANUFACTURER'S NAME: Intercon Enterprises Inc.
ADDRESS: 11-7550 River Rd.,Delta, BC V4G 1C8 Canada
EMERGENCY PHONE: Call Chemtrec 1-800-424-9300 (spill, leak, fire, accident)
INFORMATION PHONE: 1 800 665-6655
NAME OF PREPARER: Rudd Company, Inc.

=====
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION
=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg @ TEMP		PERCENT
PROPYLENE GLYCOL ACGIH TLV: Not Est. OSHA PEL: Not Est. Other: 400 ppm	57-55-6			2
TRIHIDROXYTRIETHYLAMINE ACGIH TLV: 5 mg/m3 OSHA PEL: Not Est.	102-71-6	10	205	2

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

=====
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
=====

BOILING RANGE: 370 - 635 DEG. F
DENSITY: 8.02 lb/gl
V.O.C.: 1.19 lb/gl 143 g/l (less water and exempt solvents)
.280 lb/gl 33. g/l (Emitted VOC)
LB HAP/ LB SOLIDS: .
LB VOC/LB SOLIDS: .163
SOLIDS % BY WEIGHT: 21.4
VAPOR DENSITY: Heavier than air.
EVAPORATION RATE: Slow (compared to n-butyl acetate)
SOLUBILITY IN WATER: Appreciable
APPEARANCE AND ODOR: Mild odor.

=====
SECTION IV - FIRE AND EXPLOSION HAZARD DATA
=====

FLASH POINT: 218 DEG. F **METHOD USED:** theoretical
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.3 UPPER: 12.5
EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES:

Evacuate all unnecessary personnel. Use full-protective equipment including self-contained breathing apparatus. Use water spray, preferably fog, to cool closed containers to prevent pressure build-up and possible explosion. Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams or waterways.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Contents under pressure. Exposure to heat or prolonged exposure to sun may cause bursting.

===== SECTION V - REACTIVITY DATA =====

STABILITY:

Stable

CONDITIONS TO AVOID:

High temperature and humidity, ignition sources and vapor build-up.

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong Oxidizing agents Acids Bases

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Carbon Monoxide Carbon Dioxide Hydrocarbons Nitrogen Oxides

HAZARDOUS POLYMERIZATION:

Will not occur.

===== SECTION VI - HEALTH HAZARD DATA AND SYMPTOMS OF EXPOSURE =====

PRIMARY ROUTE(S) OF EXPOSURE: Inhalation, skin contact.

INHALATION:

Unknown Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
EYE CONTACT:
Contact with liquid or vapors causes severe irritation (redness, watering, itching, stinging, blurred vision) and possible cornea damage.

SKIN CONTACT:

Contact causes irritation (dryness, itching, cracking, rash and swelling).

SKIN ABSORPTION:

None known.
SWALLOWING:

Causes nausea, vomiting, diarrhea and central nervous system depression (headache, dizziness, giddiness, nausea, loss of coordination). Corrosive! Causes burns. May be harmful or fatal.

CHRONIC EFFECTS FROM LONG TERM EXPOSURE:

Contains ingredients suspected of causing or known to cause damage to: CARCINOGEN:

NTP CARCINOGEN: No

IARC MONOGRAPHS: No

OSHA REGULATED: No

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE:

Respiratory tract irritation, nausea, eye disorders, skin disorders, sensitization to chemical substances.

===== **SECTION VII - EMERGENCY AND FIRST AID PROCEDURES**=====

INHALATION:

If affected by breathing odors or vapors, remove to fresh air. Get medical attention if symptoms persist.**EYE CONTACT:**
Immediately flush with large amounts of water for at least 15 minutes, while lifting upper and lower eyelids. Get medical attention immediately.

SKIN CONTACT:

Immediately wash with soap and water. Remove contaminated clothing and shoes. Wash or clean thoroughly before reuse. Get medical attention if irritation persists.

SWALLOWING:

In case of accidental ingestion call Poison Control Center (1-800-222-1222) or physician immediately.**OTHER:**
Have Material Safety Data Sheet available when calling Poison Control Center (1-800-222-1222) or physician; or when going to the emergency room.

===== **SECTION VIII - SAFE HANDLING AND USE INFORMATION**=====

RESPIRATORY PROTECTION:

Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's instructions for use.

VENTILATION:

USE ONLY WITH ADEQUATE VENTILATION. Open all doors and windows to achieve cross-ventilation, in work and surrounding areas, during and after application until all vapors (fumes) are gone.

HAND PROTECTION:

Wear gloves to avoid skin contact.

EYE PROTECTION: Wear safety glasses or goggles to protect eyes from splash and spray mists. Note: Contact lenses may contribute to the severity of an eye injury and should not be worn when working with chemical products.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Wear protective clothing to avoid skin contact with liquid or mists.

WORK/HYGIENIC PRACTICES:

Wash hands after using and before eating, drinking or using tobacco products. Thoroughly clean contaminated clothing and shoes before reuse.

===== **SECTION IX - SPILL AND LEAK PROCEDURES**=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate ignition sources and ventilate area. Evacuate unnecessary personnel. Wear full protective equipment. Dike and

contain spill with inert material. Transfer liquid to containers for disposal or recovery. Prevent material from entering storm drains or sanitary sewers and open bodies of water.

WASTE DISPOSAL METHOD:

Waste material and empty containers must be disposed of in accordance with all local, state and federal environmental control regulations. Use only approved waste management facilities.

===== SECTION X - SPECIAL PRECAUTIONS =====

KEEP OUT OF REACH OF CHILDREN.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Keep liquid spray and vapors away from heat, sparks and flame. Turn off or remove all sources of ignition. Use proper methods of ventilation to prevent vapor build-up. Avoid spraying hot surfaces. Avoid breathing vapors, spray mists and sanding or grinding dusts. Avoid contact with eyes and skin. Do not take internally. Use adequate methods of ventilation, respiratory and personal protective equipment. Do not reuse, weld, drill or heat empty containers which may contain explosive vapors. Follow label warnings until thoroughly cleaned or sent for disposal. Do not heat, puncture or incinerate containers. Contents are under pressure and may contain vapors even when empty. Do not remove or deface label.

OTHER CAUTIONS:

Contents under pressure. Do not store above 120 deg. F (50 deg. C) or permit prolonged exposure to sunlight. Protect containers from damage. Store in buildings or areas designed and protected for storage of aerosols.

===== SECTION XI - DISCLAIMER =====

DISCLAIMER: THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.